Doc. Ref.: AL2



Europäisches Patentamt
European Patent Office
Office européen des brevets



11 Publication number:

0 411 840 A3

(12)

EUROPEAN PATENT APPLICATION

(2) Application number: 90308260.0

(9) Int. Cl.5: **G01R** 33/36, G01R 33/54

② Date of filing: 27.07.90

Priority: 04.08.89 US 389456

① Date of publication of application: 06.02.91 Bulletin 91/06

Designated Contracting States:
 CH DE FR GB LI NL

Date of deferred publication of the search report: 03.07.91 Bulletin 91/27


Applicant: GENERAL ELECTRIC COMPANY 1 River Road Schenectady, NY 12345(US) inventor: Stormont, Robert Steven 21675 Cologne Road Waukesha, Wisconsin 53186(US) Inventor: Anas, Michael Charles N105 W16452 Prairie Way Germantown, Wisconsin 53022(US) Inventor: Pelc, Norbert Joseph 1641 Mountain Avenue Wauwatosa, Wisconsin 53213(US)

Representative: Pratt, Richard Wilson et al London Patent Operation G.E. TECHNICAL SERVICES CO. INC. Burdett House 15/16 Buckingham Street London WC2N 6DU(GB)

Radio frequency receiver for a NMR instrument.

a baseband image information signal from which two quadrature component signals are derived. An intermediate frequency section mixes (303, 306) the received NMR signal with two reference signals (201, 204) to shift the image information into a frequency band having a bandwidth BW and centered at a frequency that is 1:5 times the bandwidth BW. The resultant signal is filtered (308) to remove extraneous signals outside the image information band. An ana-

log to digital converter (209) samples the filtered signal at a rate that is twice the bandwidth Bw and digitizes the samples into a digital signal. A quadrature detector (210) derives I and Q output signals from the digital signal by alternately selecting (311, 321) digital samples and negating every other sample selected for each of the I and Q output signals. The quadrature detector also digitally filters (312, 322) the I and Q signals which are then used to construct an NMR image.





EUROPEAN SEARCH REPORT

Application Number

EP 90 30 8260

D	OCUMENTS CONS	SIDERED TO BE RI	ELEVA	NT	
Category		rith indication, where appropriate, levant passages		Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. CI.5)
A	EP-A-0 307 989 (PHILIPS PATENTVERWALTUNG Gn * Column 2, line 18 - column 3, line 42; column 4, line 2 column 6, line 56; figures 2,3 *			1,6,7,13	G 01 R 33/36 G 01 R 33/54
A	EP-A-0 292 064 (N.V. PHILIPS GLOEILAMPEN-FABRIEKEN) * Column 2, line 41 - column 3, line 31; column 8, line 18 - column 9, line 26; figure 4 *		1	1,7,11-13	
P,A	EP-A-0 336 479 (PHILIPS PATENTVERWALTUNG GmbH) * Column 1, line 36 - column 3, line 16; column 4, line 4 - column 6, line 16; figures 2,3 *			1,2,5,7, 13,14,16	
A	JOURNAL OF PHYSICS E: SCIENTIFIC INSTRUMENTS, vol. 14, 1981, pages 1253-1256, Dorking, GB; F. MOMO et al.: "Microcomputer based phase sensitive detector" Pages 1253-1255, chapters 1,2,3; figures 1-5 *			1-3,8, 13-15	
A E. FUKUSHIMA et al.: "Expe pages 60-76, Addison-Wesle US; chapter: "Quadrature de " Pages 60-64 "		sley Publishing Co., Inc., Rea		1,7,13	TECHNICAL FIELDS SEARCHED (Int. CI.5)
			-		
	The present search report has	been drawn up for all claims			
Place of search The Hague O4 April 91			rch l		Examiner
				VOLMER J.W.	
Y: p d A: te O: n P: in	CATEGORY OF CITED DOC articularly relevant if taken alone articularly relevant if combined wi ocument of the same catagory achnological background on-written disclosure itermediate document teory or principle underlying the in	th another (the filing cocume docume	g date nt cited in the nt cited for ot	her reasons